



JIANGXI HITO CHEMICAL CO.,LTD

No 6 Tianhong road,Xinghuo

industry zone,Yongxiu,

Jiujiang,Jiangxi province,China

(86)792-3170318(Tel) (86) 792-3170355 (Fax)

TECHNICAL DATA SHEET

**H-204**  
Water soluble silicone oil

**CAS:68937-55-3**

**DESCRIPTION**

**H-204** is higher viscosity polyether modified silicone oil, a non-ionic, has a low surface tension and good water solubility and emulsifying properties, is an ideal material such as silicone oil emulsifier; the product also has anti-static, soft smoothness , chemical stability and physical inertia.

**Equivalent:**Dow Corning-190

Momentive Silwet L-7087,L-7230

**TYPICAL PROPERTIES**

Appearance	Colorless or light yellow transparent liquid
Viscosity (25℃)	800-3000mPa.s
Active component	100%
Cloud point	40-50℃

**USES AND APPLICATION**

Widely used in the daily work of surfactants, textile finishing, coating additives.

**SAFETY**

Before handling, read the Material Safety Data Sheet and container label for safe use, physical and health hazard information.

**STORAGE AND SHELF LIFE**

After sealing packaging products stored in a cool, dry place , **H-204** has a shelf life of 36 months from date of manufacture.

**PACKAGING**

**H-204** is available in 200L drum and 1000L IBC or others.

**LEGAL DISCLAIMER**

Hito chemical believes that the information in this technical data sheet is an accurate description of the typical uses of the product. Hito Chemical , however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.



is a registered trademark of Hito chemical , China.